


**NOTES:**

1. PAVER WIDTH VARIES PER PLAN - PRECISE WIDTH TO BE FIELD VERIFIED TO PREVENT CUTTING OF PAVERS.
2. PRIOR TO INSTALLING CONCRETE BASE AND CURBS, CONTRACTOR SHALL SUBMIT SHOP DRAWING OF ACTUAL LAYOUT (MOCK-UP) OF PAVERS BASED ON TYPICAL INSTALLATION SHOWN ABOVE.
3. SEE STANDARD PLAN 3261 FOR TYPICAL SECTION A-A.
4. GRANITE PAVERS SHALL BE SUBSTITUTED FOR CONCRETE PAVERS WHEN DIRECTED BY CITY ENGINEER.

	<p><b>City of Bremerton</b></p> <hr/> <p><b>PUBLIC WORKS</b></p> <hr/> <p><b>ENGINEERING DIVISION</b></p>	<p><b>CONCRETE UNIT PAVER CROSSWALK</b></p> <p><b>PLAN</b></p> <p><b>DOWNTOWN LOCATIONS</b></p> <p style="font-size: small;">Alteration of this drawing is prohibited. Any approval of an altered drawing is unauthorized and void.</p>	<p><b>3260</b></p> <p><b>Revision Date</b> 8/15/08</p>